

Kodak

DC290 Zoom Digital Camera



The Ultimate Intelligent digital camera for the demanding user

The KODAK DC290 Zoom Digital Camera takes brilliant, dazzling pictures, thanks to 3.3 *Ultra* Resolution delivering 2240 x 1500 pixels per image, 2.1 non-interpolated. But what makes it the ultimate in digital flexibility and control is its ability to “learn” scripts and applications—much like you’d customise your PC with different software applications. Adjust, edit and apply special effects. Control and customise camera settings. Create animations. All right inside the camera. Whether it’s for the most demanding business applications or sophisticated personal use, the DC290 is one very smart purchase.

✓ Stunning 8" x 10" Prints

Two-megapixel resolution, capturing 1792 x 1200 pixels per image, delivers enough detail for dazzling, photo-realistic 18 x 24cm prints. *Ultra* resolution lets you make even larger prints! You won’t run short on detail when your pictures have to make a big impact.

✓ 3X Optical Plus 2X Digital Zoom

Lens optically extends to 3X with no loss in quality, plus camera can “digitally” zoom an additional 2X for added flexibility.

✓ Superior Intelligence And Control

DIGITA™ Scripting - The camera’s on-board operating system gives customised flexibility. Automating camera settings according to surrounding conditions, step-by-step guided picture taking and creating new camera functionality such as in-camera Adobe-type filters reduces errors and increases productivity.

✓ More Features, More Flexibility

Auto/manual exposure, external flash sync, burst mode - for taking sequential pictures, time-lapse mode to take a sequence of pictures at consistent time intervals. You get more picture-taking options.

✓ USB Support For Faster Downloads

Less waiting and faster results, with full USB support that lets you download up to 10X faster than serial interfaces.

✓ Upgradable Over The Internet

As new features and capabilities evolve, you’ll be able to update the DC290 over the Internet. It’s fast, easy and incredibly convenient.



DC290 Zoom Digital Camera

Kodak

DC290 Zoom Digital Camera

SPECIFICATIONS

CCD Resolution	1901 x 1212 pixels
Image Resolution	2240 x 1500 pixels (Ultra), 1792 x 1200 pixels (high), 1440 x 960 pixels (medium), 720 x 480 pixels (standard)
Image Quality Settings	Good, Better, Best, Uncompressed
Image Storage	KODAK Picture Card included
Viewfinder	50mm TFT colour LCD for review and preview, plus real-image optical viewfinder
Lens	Auto focus 3X true optical glass zoom
Digital Enhancement	2X digital zoom
Lens Focal Length	38 mm to 115 mm equivalent; 37 mm threads for optional lenses via Optional Lens Adapter
Focus Distance	0.3 m to infinity
Exposure	Auto, or manual override (+/- 2 EV in 0.5-EV increments) with manual mode white balance, exposure lock, focus distance and exposure time
Shutter Speed	1/400 to 16 second
Aperture Range	Wide: f/3.0 to f/15.3; Tele: f/4.7 to f/16.0
ISO Equivalent	100

Scripting	DIGITA text-based language, extends functionality by automating camera
Burst Capture	Max 5 pictures at high and medium res, max 20 pictures at standard res, frame rate selectable from 0.1 to 3 frames per second
Time Lapse	Set to capture shots at pre-defined intervals; playback as movie on camera or computer
Auto-Orientation Sensor	Automatically rotates image right-side up on LCD and host
Picture Overlay	Time and date stamp, date, text, logo/graphic
Albums	In-camera albums keep pictures organised
Self-Timer	10 seconds
Tripod Mount	Standard
Flash	Strobe flash (auto, red-eye, fill, off), range up to 3.0 m; flash sync capability
File Formats	JPEG (EXIF), TIFF
User Interface	Graphical, menu-driven, easy to navigate
Video Out	NTSC and PAL (user selectable)
Audio	Record and playback

Interface	USB standard (serial and IrDA connectivity available)
Power	4 AA batteries (included) or optional AC adapter
Dimensions	118 mm (w) x 57 mm (d) x 106 mm
Certifications	VCCI, CE, FCC Class B, CE Mark
Weight	525 g without batteries
Warranty	One year (or as local jurisdiction requires)

SYSTEM REQUIREMENTS

WINDOWS Systems:

- WINDOWS 95, 98 or NT 4.0 Software (to use USB, must have WINDOWS 98)
- PENTIUM 90 MHz or greater processor
- 16 MB or more of RAM (32 MB of RAM for NT 4.0)
- 120 MB of hard disk space available
- CD-ROM drive for software installation
- 256-colour monitor (16-bit colour recommended)
- Available serial port, USB port IrDA connection or PC card reader

MACINTOSH Systems:

- Power MACINTOSH System, MAC OS 7.6 or later (serial); MAC OS 8.5 or later (USB)
- 32 MB or more of RAM
- 70 MB of hard disk space available
- CD-ROM drive for software installation
- 256-colour monitor (16-bit colour recommended)
- Available serial port, USB port, or PC card reader

PACKAGE CONTENTS

- KODAK DC290 Zoom Digital Camera with handstrap and lens cover
- KODAK Picture Card
- 4 AA alkaline batteries
- 4 AA Ni-MH rechargeable batteries and charger
- USB cable for use with WINDOWS and MACINTOSH Systems
- Audio/video cable
- Quick setup guide, user's guide, registration cards

CD-ROMs with software, including:

- PHOTODELUXE Software and PAGEMILL Software from Adobe Systems, Inc. (WINDOWS and MACINTOSH)
- TWAIN Acquire Module (WINDOWS)
- WINDOWS 95, 98 and NT 4.0 Mounter
- PHOTOSHOP-compatible plug-in (MACINTOSH)
- Picture Transfer application (MACINTOSH)



Kodak, and Take Pictures. Further. are trademarks. Because of our constant endeavour to improve quality and design, modifications may be made to products from time to time. Details of stock availability and specifications given in this publication are subject to change without notice. All weights and dimensions are approximate.

ORDERING INFORMATION/ACCESSORIES

Product Name	DC200 Series Premium Camera Bag	809 2710
DC290 Zoom Digital Camera (English/European)	DC280/DC290 All-Weather Camera Bag	855 5559
(English/Italian/Spanish)	GPS Connection Kit	841 7198
(French/German)		
Recommended Accessories	CAT No.	
64 MB Picture Card	140 4169	
48 MB Picture Card	142 0629	
48 MB Picture Card w/adaptor	187 7919	
32 MB Picture Card	180 6900	
32 MB Picture Card w/adaptor	196 4840	
20 MB Picture Card	146 8628	
20 MB Picture Card w/adaptor	824 2026	
10 MB Picture Card	863 3828	
10 MB Picture Card w/adaptor	849 2399	
4 MB Picture Card	821 6822	
4 MB Picture Card w/adaptor	196 4956	
Picture Card Adapter	156 1596	
Battery Charger with 4 Ni-MH AA Batteries (UK)	867 9933	
(European Version)	852 2344	
USB Card Reader	876 4714	
DC200 Series AC Adapter	190 9282	
DC290 Lens Adapter	867 5027	
DC280/DC290 Telephoto Lens	179 2860	
DC280/DC290 Close-up Lens	138 2175	

KODAK Accessories help make this great camera even better. Visit us at www.kodak.com/go/accessories

For more information on our range of Kodak Digital products call:

Austria/Österreich	0179 567 357
Belgium/Belgique	02 713 14 45
Denmark/Danmark	3 848 71 30
Eire	01 407 3054
Finland/Suomi	0800 1 17056
France	01 55 1740 77
Germany/Deutschland	069 5007 0035
Italy/Italia	02 696 334 52
Netherlands/Nederland	020 346 9372
Norway/Norge	23 16 21 33
Spain/España	91 749 76 53
Sweden/Sverige	08 587 704 21
Switzerland/Schweiz/Suisse	01 838 53 51
UK	0870 2430270

Calls are charged @ National Rate

International Toll Line:	+44 (0) 131 458 6714
International Fax Line:	+44 (0) 131 458 6962

www.kodak.com/go/dc290

TAKE PICTURES. FURTHER.™

